

# US INTERNATIONAL

Trade+Marketing GmbH

## TECHNICAL INFORMATION SURGICAL MASK 61604

- High efficiency
- Multi-layered
- Splashproof
- Antibacterial
- Antistatic
- TÜV certified



## SURGICAL MASK

EARBAND TYPE



## SURGICAL MASK 61604



High Performance Polypropylen Surgical Mask, Earband Type, 17cm x 9cm

- Multi-layered, three layers
- Antibacterial
- Antistatic
- High efficiency
- Comfortable
- Splash proof
- No glue
- Safe

Made from 5 parts:

- Surface layer made from non-woven spunbond
- Filter layer made from non-woven meltblown material
- Bottom layer made from non-woven spunbond
- Nose clip made from moldable materials achieving 3D shaping feature
- Earloops made from Spandex plastic material

Sealed and sterilized by means of EtO Ethylenoxid sterilization process.

Storage up to 3 years at -5 to +35 C° at a maximum of 80% humidity in non-corrosive ambience under good ventilation.

Authorized representative in the European Community

**EC certified by TÜV Süd** under quality assurance system as per Directive 93/42/EEC on Medical Devices in accordance with MDD Annex V. (Devices in class I in sterile conditions, sterilized systems or procedure packs) valid until 03.02.2021

**DAkKS Deutsche Akkreditierungsstelle , TÜV Süd certified as per EN ISO 13485:2016 Medical Devices** – Quality management systems – Requirements for regulatory purposes DIN EN ISO 13485:2016 valid until 19.01.2021

# SURGICAL MASK 61604

Product information		
Product	Surgical Mask	
Model	61604	
Type	with earloops	
Size	17 x 9 cm (tolerance +/- 1%)	
Lenght Earloop	both sides 15 cm (tolerance +/- 2%)	
Weight	≥ 20g / m <sup>2</sup>	
Construction	three layers	
Colour	blue	
Quality Features	<ul style="list-style-type: none"> <li>■ Multi-layered</li> <li>■ Antibacterial</li> <li>■ Antistatic</li> <li>■ High efficiency</li> <li>■ Comfortable</li> <li>■ Splash proof</li> <li>■ No glue</li> </ul>	
Material	Polypropylen	
	Surface layer	non-woven spunbond
	Filter layer	non-woven meltblown materia
	Bottom layer	non-woven spunbond
	Nose clip	moldable materials
	Earloops	flexible Spandex plastic material
Bacterial filtering efficiency	BFE ≥99%	
Particular matter filtering capacity	high PM, ≥ 90%	
Fluid resistance	up to 2ml	
Lateral spray test performance	16.0kPa (120 mm Hg)	
Storage	up to 3 years at -5 to +35 C° at max 80% humidity in non-corrosive ambience under good ventilation	

Packing	
Quantity inner packing (Plastic bag)	25 pcs
Quantity inner packing (Carton box containing 2 bags)	50 pcs
Quantity outer carton	2000pcs weight 12,5kg/ carton
Quantity CCG1 (LxWxH incl. 15cm pallet)	24000pcs (12 outer cartons) 126x114x99cm
Quantity CCG2 (LxWxH incl. 15cm pallet)	36000pcs (18 outer cartons) 126x114x141cm
Outer dimensions outer carton in cm	57,0 x 42,0 x 42,0
Volume outer carton in cbm	0.100548
Grossweight outer carton in kg	12,5
Customs tariff number	6307909810

# US INTERNATIONAL

Trade+Marketing GmbH

Mattentwiete 5  
20457 Hamburg  
Germany

 +49 40 280 967 55

 +49 40 280 967 56

 mail@us-international.one